

Netac

ZX20 II

USB 3.2 Type-C

Magnetic Portable SSD



DATA SHEET

Speed Storage, Magnetic Stability

The ZX20 II Magnetic Portable SSD seamlessly blends high-speed performance with innovative magnetic functionality, providing an ideal storage solution for professionals on the go. With a read speed of up to 2000MB/s, it delivers rapid file transfers, making it perfect for 4K video editing, large file backups, and fast data access. The integrated magnetic design ensures easy attachment to metallic surfaces, offering unparalleled convenience and portability without compromising security. Compact and durable, the ZX20 II combines robust performance, high storage capacity, and a rugged exterior to keep your data safe and accessible, wherever your work takes you.

Feature

- 2000MB/s speed for fast file transfers
- Magnetic attachment for secure use
- Up to 2TB storage for all your files
- 4K ProRes recording with iPhone support
- Plug-and-play Type-C for easy setup
- Compact and durable design for portability
- Data encryption for secure file management

*iPhone 6-14 users with Lightning ports cannot connect directly to this storage device.

Specification

Interface	USB 3.2 Type-C
Capacity	512GB/1TB/2TB
Transmission Speed	up to 2000 MB/s
Storage Temperature	-40°C~85°C
Operation Temperature	0°C~70°C
Color	Black
Material	Alloy + Silicone
Weight	About 47g
Dimension (L x W x H)	78 x 46 x 8 mm
Service & Support	5-Year Limited Warranty

Ordering Information

Capacity	Part Number
512GB	NT01ZX20II-512-32BK
1TB	NT01ZX20II-1T0-32BK
2TB	NT01ZX20II-2T0-32BK

*Test data are provided by Netac's laboratory and are for reference only. Performance read/write varies by system performance and capacity.

*When using an external storage device, please make sure that it is connected through the correct port to ensure operational performance.

*For full details please visit www.netac.com or consult your distributor.

Netac Technology Co., Ltd

18F, Netac Building, Number 6 High-tech South St, Nanshan District, Shenzhen | Tel: 86-755-26727516 | Mail: sales@netac.com
Features and specifications are subject to change without notice. Pictures shown may vary from actual products.
The total accessible capacity varies depending on the operating environment.
All brand names are registered trademarks of their respective owners.
Netac Technology Co., Ltd. All rights reserved. | June 2025

